

### 概述 Summary

- > 单组输出: 功率 3000w  
Single output: power 3000w
- > 输入电压: 200 ~ 264VAC  
Input voltage: 200 ~ 264VAC



291 x 132 x 136mm

### 常见规格 General Specification

| 性能 Specification                            | 型号 Model | S-3000-24  | S-3000-27  | S-3000-36 | S-3000-48   |
|---|----------|--|------------|-----------|-------------|
| 直流输出电压、电流<br>DC output voltage, current     |          | 24V 0~125A   | 27V 0~111A | 36V 0~83A | 48V 0~62.5A |
| 纹波及噪音<br>Wave and noise                     |          | 120mVp-p   | 200mVp-p   | 200mVp-p  | 240mVp-p    |
| 进线稳定度<br>Inlet wire stability               |          | ± 0.5%   | ± 0.5%     | ± 0.5%    | ± 0.5%      |
| 负载稳定度<br>Load stability                     |          | ± 0.5%   | ± 0.5%     | ± 0.5%    | ± 0.5%      |
| 效率<br>Efficiency                            |          | 80%  | 85%        | 86%       | 87%         |
| 直流电压可调范围<br>Adjustable range for DC voltage |          | ± 10%  | ± 10%      | ± 10%     | ± 10%       |
| 输入电压范围<br>Input voltage range               |          | 200 ~ 264VAC<br>200 ~ 264VAC   |            |           |             |
| 冲击电流<br>Impact current                      |          | 冷启动电流 45A/230VAC<br>Cold start current   |            |           |             |
| 过载保护<br>Overload protection                 |          | 105% ~ 135%切断输出, 自动恢复<br>105% ~ 135% cut off the output, automatic recovery                        |            |           |             |
| 启动、上升、保持时间<br>Setup, rise, hold up time     |          | 2000ms, 50ms, 20ms/230VAC 满负载 at full load   |            |           |             |
| 耐压性<br>Withstand voltage                    |          | 输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟<br>I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute |            |           |             |
| 隔离电阻<br>Isolation resistance                |          | 输入输出间 输入与外壳间 输出与外壳间: 500VDC/100MΩ<br>I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ                           |            |           |             |
| 工作温度<br>Working temperature                 |          | -10°C ~ +50°C  |            |           |             |
| 尺寸<br>Dimension                             |          | 291 x 132 x 136mm  |            |           |             |
| 重量<br>Weight                                |          | 5.3kg  |            |           |             |
| 包装<br>Packing                               |          | 38 x 37.5 x 21CM/2PCS/11kg   |            |           |             |

### 外形尺寸 Overall dimension(mm)

